



Safety Data Sheet: FIBRE GLASS HARDENER

Product Name	: FIBRE GLASS HARDENER
Product Code	: G61815
Revision Date	: 16/02/2015
Revision Number	: 1

Company	: Force Products Ltd
Address	: Stock House, Seymour Road Nuneaton Warwickshire CV11 4LB
Telephone	: 0044 (0)2476322130
Fax	: 0044 (0)2476322151
Email	: sales@forceproducts.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC/1272/2008)

Physical hazards Org. Perox. C - H242

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Acute 1 - H400

Classification (67/548/EEC or 1999/45/EC)

Xi;R36. R43. O;R7. N;R50.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements

H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.



Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P235 Keep cool.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
- P337+P313 If eye irritation persists: Get medical advice/ attention.
- P411 Store at temperatures not exceeding 25°C/77°F.
- P501 Dispose of contents/ container in accordance with local regulations.

Contains BENZOYL PEROXIDE

Supplementary precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P220 Keep away from combustible materials.
- P234 Keep only in original container.
- P261 Avoid breathing vapour/spray.
- P264 Wash contaminated skin thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P313 Get medical advice/ attention.
- P321 Specific treatment (see medical advice on this label).
- P337 If eye irritation persists:
- P363 Wash contaminated clothing before reuse.
- P391 Collect spillage.
- P410 Protect from sunlight.
- P420 Store away from other materials.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures



BENZOYL PEROXIDE	30-60%
CAS number: 94-36-0	EC number: 202-327-6
Classification Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Acute 1 - H400	Classification (67/548/EEC or 1999/45/EC) Xi;R36. O;R7. N;R50. E;R3. R43.
DIMETHYL PHTHALATE	30-60%
CAS number: 131-11-3	EC number: 205-011-6
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air at once. Get medical attention.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.

Ingestion DO NOT induce vomiting. Get medical attention immediately.

Skin contact Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart.

Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information

Effects may be delayed. Keep affected person under observation.

Inhalation No specific symptoms known.

Ingestion No specific symptoms known.

Skin contact No specific symptoms known.

Eye contact No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media



Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Carbon dioxide (CO₂). Carbon monoxide (CO).

Hazardous combustion products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces. Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination. Do not discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid the formation of mists. Provide adequate ventilation. Read and follow manufacturer's recommendations. Do not handle broken packages without protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store away from the following materials: Reducing agents. Acids.



Alkalis. Protect from freezing and direct sunlight. Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

BENZOYL PEROXIDE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL

DIMETHYL PHTHALATE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL 10 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Neoprene. Nitrile rubber. Polyethylene.

Polyvinyl chloride (PVC).

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures Wash contaminated clothing before reuse. Wash promptly with soap and water if skin becomes contaminated. Wash hands after contact. When using do not eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Paste.



Colour Various colours.
Odour Characteristic.
pH Not determined.
Melting point Not determined.
Initial boiling point and range Not determined.
Flash point Not determined.
Evaporation rate Not determined.
Upper/lower flammability or explosive limits Not determined.
Vapour pressure Not determined.
Vapour density Not determined.
Solubility(ies) Insoluble in water.
Partition coefficient Not determined.
Auto-ignition temperature Not determined.
Decomposition Temperature Not determined.
Oxidising properties Not available.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions

Avoid contact with acids and alkalis. Avoid heat.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with the following materials: Oxidising agents. Reducing agents. Avoid contact with acids and alkalis. Reactions with the following materials may generate heat: Alkalis. Amines.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Amines. Acids - oxidising. Alkali metals. Alkaline earth metals.

10.6. Hazardous decomposition products

Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon.

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.



SECTION 12: Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

12.1. Toxicity

Acute toxicity - fish LC50, 96 hours: 0.0602 mg/l, *Onchorhynchus mykiss* (Rainbow trout)

Acute toxicity – aquatic invertebrates

Not available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3269

UN No. (IMDG) 3269

UN No. (ICAO) 3269

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

POLYESTER RESIN KIT

Proper shipping name (IMDG) POLYESTER RESIN KIT

Proper shipping name (ICAO) POLYESTER RESIN KIT

Proper shipping name (ADN) POLYESTER RESIN KIT



14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID label 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

14.6. Special precautions for user

EmS F-E, S-D

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.



Revision date 16/02/2015

Revision 12

Supersedes date 28/04/2014 v11

SDS status Approved.

Risk phrases in full R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.

R36 Irritating to eyes.

R43 May cause sensitisation by skin contact.

R50 Very toxic to aquatic organisms.

R7 May cause fire.

Hazard statements in full

H241 Heating may cause a fire or explosion.

H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

This data sheet is compiled to be of assistance but without guarantee. Users are responsible for safe working practices. Final determination of suitability of any material is the sole responsibility of the user.