



**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

PRE-BUFF CLEANER

**Art.-No.**

PPC-32 (SKU No. 2207030); PPC-5000 (SKU No. 2207050)

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Cleaning agent

**1.3. Details of the supplier of the safety data sheet**

Company name: PREMA GmbH  
Street: Aspertscham 40  
Place: D-94081 Fürstentzell  
Telephone: +49 (0) 8502 917 150 0  
Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone**

**number:** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24  
24

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

Indications of danger: F - Highly flammable, Xn - Harmful, N - Dangerous for the environment

R phrases:

Highly flammable.

Irritating to skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

**Hazardous components which must be listed on the label**

Naphtha (petroleum)

Signal word:

Danger

Pictograms:

GHS02-GHS07-GHS08-GHS09



**Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

**PRE-BUFF CLEANER**

00623-0003

H336 May cause drowsiness or dizziness.  
 H304 May be fatal if swallowed and enters airways.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P261 Avoid breathing vapour.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P243 Take precautionary measures against static discharge.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P331 Do NOT induce vomiting.  
 P273 Avoid release to the environment.  
 P391 Collect spillage.

**2.3. Other hazards**

Vapours may form explosive mixture with air.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Preparation solved in petroleum spirit

**Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
265-151-9	Naphtha (petroleum)	> 95 %
64742-49-0	F - Highly flammable, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R11-38-51-53-65-67	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	

Full text of R-, H- and EUH-phrases: see section 16.

**Further Information**

According to note P to the regulation (EC) no. 1272/2008, "Naphtha (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
 In the event of persistent symptoms receive medical treatment.  
 Take away from danger area and lay down affected person.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.  
 If you feel unwell, seek medical advice.

**After contact with skin**

Wash off with soap and plenty of water.  
 Treat subsequently with skin cream.  
 Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
 Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.  
 Summon a doctor immediately.  
 Induce vomiting only upon the advice of a physician.



---

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

---

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

##### **Unsuitable extinguishing media**

Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:

Carbon monoxide and carbon dioxide

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.

Protective suit.

##### **Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Use personal protective clothing.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

---

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

##### **Advice on protection against fire and explosion**

Do not smoke - volatile.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

#### **7.2. Conditions for safe storage, including any incompatibilities**



**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.

**Advice on storage compatibility**

Incompatible with oxidizing agents.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

Cleaning agent

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**8.2. Exposure controls**

**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).

**Hand protection**

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Solvent-resistant apron (EN 467).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	Colourless	
Odour:	Hydrocarbon-like	
Melting point:	< - 20 °C	ASTM D 97
Initial boiling point and boiling range:	63 - 100 °C	ASTM D1078
Flash point:	< - 26 °C	ASTM D 56
Lower explosion limits:	1,1 vol. %	
Upper explosion limits:	~ 7,4 vol. %	
Vapour pressure: (at 20 °C)	24,58 hPa	
Vapour density:	> 1	
Density (at 15 °C):	0,7 g/cm³	ASTM D 4052
Water solubility: (at 20 °C)	Immiscible (< 1 %) g/L	
Ignition temperature:	> 200 °C	



---

Viscosity / dynamic:	< 0,38 mPa·s	ASTM D 445
Solvent content:	100 %	

**9.2. Other information**

No data available.

---

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

**10.4. Conditions to avoid**

At standard pressure, distillable without decomposition.

In use formation of flammable/explosive vapour-air mixtures possible.

**10.5. Incompatible materials**

oxidizing agents

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

---

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Naphtha (petroleum)

LD50/oral/rat: > 2000 mg/kg

LD50/dermal/rabbit: > 2000 mg/kg

LC50/inhalation/rat: > 5 mg/l

**Irritation and corrosivity**

Causes skin irritation.

Eye irritation: Not classified.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Naphtha (petroleum) )

**Severe effects after repeated or prolonged exposure**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

**Practical experience**

**Other observations**

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Hazard of lung oedema.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

---

**SECTION 12: Ecological information**



**PRE-BUFF CLEANER**

00623-0003

**12.1. Toxicity**

EC50 Ecological data are not available.

Naphtha (petroleum)

LC50/EC50/EC50 : 1 - 10 mg/l

Toxic to aquatic life with long lasting effects.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

**12.6. Other adverse effects**

Low hazard to waters.

**Further information**

Do not flush into surface water or sanitary sewer system.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Advice on disposal**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

**Waste disposal number of waste from residues/unused products**

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (except 07 and 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures  
Classified as hazardous waste.

**Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:** UN1263  
**14.2. UN proper shipping name:** Paint related material  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number:** UN1263  
**14.2. UN proper shipping name:** Paint related material  
**14.3. Transport hazard class(es):** 3



**PRE-BUFF CLEANER**

00623-0003

**14.4. Packing group:** II

Hazard label: 3



Classification code: F1

Limited quantity: 5 L / 30 kg

**Marine transport (IMDG)**

**14.1. UN number:** UN1263

**14.2. UN proper shipping name:** PAINT RELATED MATERIAL (Naphtha (petroleum))

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Marine pollutant: Yes

Limited quantity: 5 L / 30 kg

EmS: F-E, S-E

**Air transport (ICAO)**

**14.1. UN number:** UN1263

**14.2. UN proper shipping name:** PAINT RELATED MATERIAL

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3



Limited quantity Passenger: Y341 / 1 L

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes



**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

1999/13/EC (VOC): 95 - 100 %

**National regulatory information**



Employment restrictions:

Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information**

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC = Code International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**Relevant R-phrases (Number and full text)**

- 11 Highly flammable.
- 38 Irritating to skin.
- 51 Toxic to aquatic organisms.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

**Relevant H- and EUH-phrases (Number and full text)**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*